

TELESIS TWL

Thermoplastic Wet Location LED Exit Sign

The Telesis TWL is a UL wet location listed LED exit sign, featuring energy-efficient, long-lasting LEDs housed in a sleek, low-profile, UV-stabilized polycarbonate casing. Available in single or double face configurations, it includes a low-profile mounting canopy and field-selectable chevron indicators. Its quick-connect components provide fast, contractor-friendly installation and ease of maintenance.



CONSTRUCTION

- Attractive, Low Profile UV Stabilized Polycarbonate housing in a pure White, Black or Gray finish
- Vandal resistant, UV stabilized clear polycarbonate lens fully gasketed for use in wet locations
- Stainless steel captive screws secure the lens cover to the housing
- Single or double face to order, universal mounting canopy and hardware provided
- Universal mounting pattern for wall mount, with Field Selectable Chevron Directional Indicators
- Wet location listed as standard and suitable for NEMA 4X requirements

ELECTRICAL

- Exceptionally Low Energy Consumption at < 3.5 Watts avg.
- LED light source with 20+ years life expectancy
- High Intensity LED Array with 6" letter and 3/4" stroke in red or green, providing superior visual brightness and uniformity
- Field Selectable 120 or 277 VAC input
- Available with a full self-test / self-diagnostic option

- Integral AC Present Indicator and Push to Test Switch
- Electronic Control Circuit and Isolation Transformer provide current control and circuit protection ensuring optimum LED efficiency and life
- Maintenance free Nickel Cadmium Battery provides the required 90 minute minimum operating time
- Fully automatic two rate charger recharges the battery in 24 hours
- Operating temperature range -20°C to 50°C
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge
- Line-latch prevents unnecessary discharge of battery during installation

CERTIFICATION

- UL 924 listed meets NFPA 101 Life Safety Code, NFPA 70-NEC, and OSHA requirements
- California Energy Commission (CEC) Title 20 Compliant

WARRANTY

- 3 year limited warranty - view complete warranty terms online at www.evenlite.com/terms-warranty.

ORDERING GUIDE

TWL-EM-R-2U-W-SD

MODEL	OPERATION	LETTER COLOR	FACE COUNT	HOUSING COLOR	OPTIONS	ORDERING NOTES
TWL	AC AC Only (120/277V)	R Red LED	1U Single Face	W White (with White Faceplate)	SD Self-Diagnostic Testing ¹	1 For EM Units 2 Dual circuit cannot be used with two live circuits
	EM Battery Back-up Emergency	G Green LED	2U Double Face	B Black (with Black Faceplate) G Gray (with White Faceplate)	DKV1 2 Circuit Input 120VAC ² DKV2 2 Circuit Input 277VAC ² M990010 Wireguard TP Tamper-proof screws	
TWL						

Fill in fields from categories above and complete type and part number.

Type No:	Full Part No:
----------	---------------

DIMENSIONS

