EVENLITE
LIVES DEPEND ON US

Project Name:	Approved By:
Catalog No:	Type No:

WAYLIGHTER

Recessed Low Level LED Emergency Light

"The Waylighter provides a concealed, vandal-resistant LED emergency light that projects uniform illumination along the egress corridor, with spacings up to 50 feet on center. Unlike traditional ceiling or wall-mounted emergency lights, it eliminates distracting glare and light obstructions, enhancing visibility and safety. Positioned just 18 inches above the floor, Waylighter ensures a clear path to safety, even in heavy smoke conditions. Pair it with our low-level exit signs and way marking system for the ultimate emergency lighting solution.

CONSTRUCTION

- Recessed Wall mounted - just 18" above floor level
- Low profile - hinged door only 3.25" high x 7.5" wide
- Unique unidirectional drive with free floating actuation ensures free movement of door, providing trouble free operation
- Concealed mounting hardware and tamper resistant door
- Rugged 1 / 8" die cast aluminum housing - durable and vandal resistant
- Durable white powder coat textured finish (Easily field-painted or wall papered to further blend into your environment)
- Modular assembly and quick connector wiring for fast installation and easy maintenance

ELECTRICAL

- Microprocessor controlled circuit accurately calculates the door open and closed position and does not rely on preset limit switches, gears, or clutches
- Multipurpose back box suitable for installation in existing and new construction
- Solid state microprocessor controlled circuitry also includes line latch, brownout and battery LVCO
- Automatic, discreet monthly Self-Testing / Self-Diagnostics, monitors lamp load, transfer circuit, battery capacity, door operation and motor drive
- Choice of maintenance free Lead Calcium, or Nickel Cadmium batteries
- 2 Hour run time is standard for Lead Calcium and Nickel Cadmium batteries
- Infrared receiver allows remote testing with optional transmitter
- Optional Hand-held remote transmitter with selectable 30-second or 90-minute emergency test to ensure code compliance
- Discreet manual test switch and AC indicator light, test switch can initiate a 30 second or 90 minute test
- Field Selectable 120 or 277 VAC 60 HZ input

ILLUMINATION

- Purpose designed for optimum corridor illumination
- Precise LED optics and fixed Mirror arrangement ensures optimal light distribution without requirement for user field adjustment
- High output LED's (311 absolute lumens)provide unparalleled spacing in low level mounting applications with just 11 watts total load
- 50' spacing on center over 4' path of egress meets NFPA requirements

CERTIFICATION

- ADA compliant design - with door full open at only 2-3 / 8" in the emergency mode
- Meets or exceeds all performance standards as required by NFPA 101 Life Safety Code, NFPA 70-NEC and OSHA
- Tested, Approved and listed by Underwriters Laboratories Inc. to UL924 and CSA C22-2 No.141-10
- Approved for use in New York City, Calendar Number 51285
- Buy American Act compliant

WARRANTY

- 3 year limited warranty - view complete warranty terms online at www.evenlite.com/terms-warranty.

WAY-LC-UI-TD

ORDERING GUIDE

MODEL	BATTERY TYPE	MOUNTING	OPTIONS
WAY	**LC** Sealed Lead Calcium[1] **NC** Nickel Cadmium[1]	**UI** Back Box & Fixture[2] **UP** Back Box[3]	**CC** Custom Color[4] **TLRT** Infrared Remote Testing Transmitter **TD** 15 Minute Time Delay
WAY			

ORDERING NOTES
1 120 minutes
2 Shipped complete
3 Preship back box
4 Specify preference

Fill in fields from categories above and complete type and part number.

Type No:	Full Part No: