

PROJECT NAME:	APPROVED BY:
CATALOG NO:	TYPE NO:

## TELESIS - TLRC SERIES

### Remote Capable LED Exit Sign

The Telesis TLRC provides an economical compact thermoplastic LED Exit sign with an additional 6 watts battery capacity for operation of remote 9.6 Volt loads or extended unit run time (4 hours) for the Exit sign without remote loads.

#### Construction

- High impact, flame retardant injection molded thermoplastic housing available in white or black
- Snap fit together housing with universal low profile mounting canopy
- Universal Single or Double Face
- Field selectable chevron directional indicators

#### Electrical

- 6 Watt additional battery capacity (for 90 mins.) powers remote 9.6 Volt DC loads or extended Exit Sign run time of 4 hours
- Maintenance free sealed Nickel Cadmium batteries
- Field selectable 120 or 277 VAC input
- Momentary test switch and AC status indicator
- Constant voltage solid state charging circuit
- Line-latch prevents unnecessary discharge of battery during installation, loads will not illuminate until after application of utility power
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge
- Brownout sensing assures emergency operation during periods of low line voltage

#### Illumination

- Quality LED light source provides exceptional low energy consumption with extended life rated up to 25 years
- Red or Green LED's with 6" letter and 3/4" stroke





#### Certification

- UL Listed for damp locations 0° to 40° C
- UL 924 Listed, meets NFPA101 Life Safety Code, NFPA 70-NEC and OSHA requirements
- Certified to CEC under Title 20 regulations



#### Warranty

- 5 Year limited warranty, batteries pro-rated



#### ORDERING GUIDE – TLRC

Example: TLRC-RU-W-SD

Model	Letter Color	Housing Color	Options
TLRC Telesis Remote Capable LED Exit	<b>RU</b> Red Universal <b>GU</b> Green Universal	<b>W</b> White <b>B</b> Black	<b>SD</b> Self-Diagnostics/Self-Test <b>M990005</b> Wire Guard 13.5" H x 15" W x 6" D  <b>Compatible Remote Heads*</b> <b>PILED-MV</b> Single 1 Watt LED Indoor Remote Head <b>PILED2-MV</b> Double 1 Watt (ea) LED Indoor Remote Head <b>PRWLED1-MV</b> Single 1 Watt LED Outdoor Remote Head <b>PRWLED2-MV</b> Double 1 Watt (ea) LED Outdoor Remote Head <b>HL</b> 12 LED's per head 1.5 watts <i>*Remote heads must have SD when used with SD option</i>
TLRC			

Fill in fields from categories above and complete type and part number.

Type Number:

Full Part Number: