

PROJECT NAME:	APPROVED BY:
CATALOG NO:	TYPE NO:

SCHL3 - 3 WATTS METAL

Chicago Approved Steel LED Emergency Unit

SCHL3 is a Chicago Approved Steel LED Emergency Unit featuring LVD (low voltage disconnect) and internal solid-state transfer switch. The fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours. The housing is constructed from durable 20-gauge steel.

Construction

- Knockouts on the back for wall mount
- Side and top knockouts for conduit feed applications
- Durable 20-gauge steel construction
- White standard, black to order

Electrical

- Dual 120/277 selectable input voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- 6V sealed lead acid, maintenance-free, rechargeable battery
- Internal solid-state transfer switch automatically connects the internal battery to the LED lamp heads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours

Illumination

- Two 6V 3.3W LED Lampheads provide 335 lumens
- Remote capacity of 5.4W at 6VDC standard

Certification

- UL Listed for damp locations (20°C to 50°C)
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- Meets City of Chicago requirements



Warranty

- Five year limited warranty
- Battery pro-rated for two years

ORDERING GUIDE – SCHL3

Example: SCHL3-W

Model	Housing Color	Options	Compatible Remote Heads
SCHL3	W White B Black	M990005 Wire Guard 13.3/4" x 151/4 X 6" VRS-1 Polycarbonate Vandal Shield	PILED1-MV 1-watt single indoor remote head PILED2-MV 1-watt ea. double indoor remotehead PRWLED1-MV 1-watt single outdoor remote head PRWLED2-MV 1-watt ea. double outdoor remote head
SCHL3			

Fill in fields from categories above and complete type and part number.

Type Number:

Full Part Number:

