

TELESIS TLP

Thermoplastic Linear LED Combo Exit Sign

The Telesis TLP features a unique combination exit/emergency light with a linear LED array housed in an adjustable, highly reflective metalized reflector with a polycarbonate spread lens for maximum performance. The linear LED array positioned at the bottom of the sign creates a compact, high-performance exit and emergency light combination. Housed in a durable and economical ABS enclosure, the design features long-lasting, energy-efficient white LEDs that deliver bright illumination and ensure the required 90 minutes of emergency lighting.



CONSTRUCTION

- Specular reflector and linear White LED array with polycarbonate diffuser lens
- Injection Molded 5VA flame retardant, high impact thermoplastic housing in a White or Black finish
- Universal mounting canopy included for end wall or ceiling mounting, single or double face
- Snap Together, Quick Fit Installation with Field Selectable Chevron Directional Indicators
- Long Life, High Intensity LED Array available in Red or Green letters with 6" height and 3/4" stroke

ELECTRICAL

- Field Selectable 120 or 277 VAC input
- Damp location listed standard
- Available with a full self-test / self-diagnostic option
- Solid state transfer relay for reliability
- Electronic Control Circuit and Isolation Transformer provide current control and circuit protection ensuring optimum LED efficiency and life

- Two Nickel Cadmium Batteries provide 90 minute emergency run time
- Operating temperature range 0°C to 50°C
- Dual rate charger recharges the battery in 24 hours
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge
- Line-latch prevents unnecessary discharge of battery during installation
- Integral AC Present Indicator and Push to Test Switch
- 1-Watt Remote Lamp Head Capacity Standard

ILLUMINATION

- Exceptionally Low Energy Consumption LED light source with 10+ years life expectancy

CERTIFICATION

- UL 924 listed and meets NFPA 101 Life Safety Code, NFPA 70-NEC, and OSHA requirements, CEC Title 20 Compliant

WARRANTY

- 3 year limited warranty - view complete warranty terms online at www.evenlite.com/terms-warranty.

ORDERING GUIDE

TLP-EM-RU-W-SD

MODEL	OPERATION	LETTER COLOR	FACE COUNT	HOUSING COLOR	OPTIONS	ORDERING NOTES
TLP	NiCad Battery Backup 120/277 VAC	R Red G Green	2U Universal ¹	STANDARD W White B Black	SD Self-Test/Self-Diagnostic M990005 Wire Guard ²	1 Single/Double Face Universal Mount 2 Dimensions: 13.5" H x 15" W x 6" D
TLP	EM		2U			

Fill in fields from categories above and complete type and part number.

Type No:

Full Part No:

DIMENSIONS

