

| Project Name: | Approved By: |
|---------------|--------------|
| Catalog No:   | Type No:     |

# TUFFLITE SCHL

Chicago-Approved Steel LED Emergency Light

Tufflite SCHL is a Chicago Approved Steel LED Emergency Unit featuring LVD (low voltage disconnect) and internal solid-state transfer switch. The fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours. The housing is constructed from durable 20-gauge steel.



#### **CONSTRUCTION**

- Knockouts on the back for wall mount
- Side and top knockouts for conduit feed applications
- Durable 20-gauge steel construction
- White standard, black to order

#### **ELECTRICAL**

- Dual 120 / 277 selectable input voltage
- Charge rate / power "ON" LED indicator light and push-to-test switch for mandated code compliance testing
- LVD (low voltage disconnect) prevents battery from deep discharge
- 6V sealed lead acid, maintenance-free, rechargeable battery
- Internal solid-state transfer switch automatically connects the internal battery to the LED lampheads for minimum 90-minute emergency illumination
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours

#### **ILLUMINATION**

- Two 6V 3.3W LED lampheads provide 335 lumens
- Remote capacity of 5.4W at 6VDC standard

#### **CERTIFICATION**

- UL Listed for damp locations (20°C to 50°C)
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- Meets City of Chicago requirements

### **WARRANTY**

- Five year limited warranty view complete warranty terms online at <u>www.evenlite.com/terms-warranty</u>.
- Battery pro-rated for 2 years

ORDERING GUIDE SCHL3-W

| MODEL | HOUSING COLOR  | OPTIONS                           | COMPATIBLE REMOTE HEADS                          | ORDERING NOTES  1 Dimensions: |
|-------|----------------|-----------------------------------|--|-------------------------------|
| SCHL3 | B Black        | M990005 Wire Guard <sup>1</sup>   | PILED1-MV 1-Watt Single Indoor Remote Head       | 13.3/4" x 151/4 X 6"          |
|       | <b>W</b> White | VRS-1 Polycarbonate Vandal Shield | PILED2-MV 1-Watt Ea. Double Indoor Remote Head   |                               |
|       |                |                                   | PRWLED1-MV 1-Watt Single Outdoor Remote Head     |                               |
|       |                |                                   | PRWLED2-MV 1-Watt Ea. Double Outdoor Remote Head |                               |
| SCHL3 |                |                                   |  |                               |


Fill in fields from categories above and complete type and part number.

Type No:

Full Part No:









## **DIMENSIONS**

