

INSTALLATION AND OPERATING INSTRUCTIONS

IMPORTANT SAFEGUARDS!!! SAVE THESE INSTRUCTIONS!!!

READ AND FOLLOW ALL SAFETY INSTRUCTIONS

When using electrical equipment, basic safety precautions should always be followed, including the following:

1. Review the diagrams and instructions thoroughly before beginning installation.
2. All electrical connections must be in accordance with local codes, ordinances, and the National Electric code.
3. Disconnect power at the fuse or circuit breaker before installing or servicing the unit.
4. Do not mount in hazardous locations or near gas or electric heaters.
5. Do not allow power cords to be in contact hot surfaces.
6. Equipment should be mounted in locations and at heights where it will not be subjected to tampering by unauthorized personnel.
7. The use of accessory equipment not recommended by the manufacturer may cause unsafe or failed fixture operation and may void warranty.
8. Do not use this equipment for purposes other than its intended use.
9. All servicing should be performed by qualified personnel only.

NOTICE: WEAR GLOVES WHEN INSTALLING OR HANDLING

Fixed Locking Screw

Back plate

Housing / Front cover

1/2"

NOTICE : WEAR GLOVES DURING INSTALLATION!

Figure 1

NOTICE:

Keep the back plate at least 1/2 inch away from the support surface when drilling or knocking out mounting holes.

Figure 2

screws

J-box (not provided)

NOTICE:

Ensure screws are secure and not over tightened to prevent the back plate from deforming, which could affect the waterproof function.

Align

Figure 3

NOTICE:

After installation, apply silicone sealant to all exposed areas to ensure waterproofing.
Assemble the front cover onto the back plate securely.

Installation Instructions

Figure 4

1. Connect the wires to a DC 3~12V power supply in accordance with local and national codes.

2. Select the appropriate remote power switch button for 1W, 2W, or 3W operation.

3. Secure the fixture to the junction box.

Yellow (+)

Purple (-)

DC 3~12V input

1W 2W 3W