

SLIMLINE SL

Self-Luminous Tritium Exit Sign

The Slimline SL offers a sleek, architectural design in a low-profile, durable aluminum housing. Requiring no electricity, the SL is completely energy-efficient and is recyclable at the end of its life, making it an ideal solution for green buildings.



CONSTRUCTION

- 100% reliable, maintenance free and always on
- Operating temperature range -55°C to 80°C
- 6" high letters with 3/4" stroke with Red, Green or Black background available
- Hidden tamper resistant wall mounting hardware
- Aluminum stencil face with field selectable chevron directional indicators
- Optional end or ceiling mount brackets are available
- Corrosion resistant extruded aluminum .05" minimum wall thickness fold-formed to prevent tampering
- Sustainable design and fully recyclable at the end of its useful life
- Standard finish is anodized aluminum. Also available in satin white or black enamel
- Polycarbonate shield seals lamp compartment and prismatic refractor lens
- Available in service life ratings of 10, or 20 years

ELECTRICAL

- Non-electrical, internally illuminated by sealed tritium gas light sources
- Requires no external light source, electrical power, wiring or batteries

ORDERING GUIDE

SL-10-2-G-W-PA

MODEL	SERVICE LIFE	NO. OF FACES	FACE COLOR	FRAME COLOR	MOUNTING	ORDERING NOTES
SL	10 10 Years	1 Single Face	R Red	BA Brushed Aluminum	MB Mounting Bracket ¹	NOTE: For vandal resistant signs see data sheets SLV, INH or LEX 1 For Top or End Mounting
	20 20 Years	2 Double Face	G Green	B Black	PA 12" Swivel Pendant	
			B Black	W White	PB 24" Swivel Pendant	
					PC 36" Swivel Pendant	
					PD 48" Swivel Pendant	
SL						

Fill in fields from categories above and complete type and part number.

Type No:

Full Part No:

DIMENSIONS

